

PRODUCT LINE	Designa Exterior Acrylic Gloss	
DESCRIPTION	<p>A pure 100% acrylic paint. Designed to give a gloss finish with long term durability in exterior applications. Designa Acrylic Gloss utilises modern acrylic technology to give a product with exceptional performance on most exterior substrates.</p> <p>Designa Exterior Gloss comes with a 10 year guarantee.</p>	
TYPICAL USES	<p>May be used on suitably prepared:</p> <ul style="list-style-type: none"> • Weatherboards • Suitably primed timber • Plywood • Masonry • Concrete • Concrete blocks • Textured surfaces • Galvanized iron • Fibre Cement Products 	
PHYSICAL PROPERTIES	<p>Binder Type Solvent Colour Finish Dry Time Recoat time Number of Coats Theoretical Coverage Recommended Film Thickness Thinning & Clean Up</p>	<p>100% Acrylic Water White and tinted colours Gloss 30 minutes at 20°C 2 hours at 20°C 2 10-12m² per litre 100 microns per coat W.F.T Water</p>
SURFACE PREP	<p>Ensure surfaces are free from loose or flaky paint. Wash surfaces with Colourplus Blue Wash prior to painting to remove oil, grease, dirt, and other contaminants. Where there are areas of mould, treat with Colourplus Green Clean.</p>	
APPLICATION	<p>Designa Acrylic Gloss may be applied by brush, roller or spray. Airless Spray - a 415 or 417 tip is recommended for weatherboards, and a 517 tip is recommended for textured surfaces before being back rolled.</p> <p>Weatherboards – pre primed</p> <ol style="list-style-type: none"> 1. Apply 2 coats of Designa Acrylic Gloss, allow 2 hours between coats. <p>New Timber</p> <ol style="list-style-type: none"> 1. Apply 1 coat of Designa Acrylic Primer Undercoat. 2. Apply 2 coats of Designa Acrylic Gloss. Allow 2 hours between coats. <p>Repaints</p> <ol style="list-style-type: none"> 1. Sand existing paint work and spot prime bare wood as above. 2. Apply 2 coats of Designa Acrylic Gloss as above. 	

Concrete Tiles and Bricks

1. Prime with Keycote. Allow 4 hours drying time.
2. Apply 2 coats of Designa Acrylic Gloss.
If tiles are very porous, they may require waterproofing with Designa FMC Flexible Membrane Coating.

Concrete blocks and Reinforced Concrete

1. Where porous, seal with Designa Blockseal thinned with water 50/50.
2. Apply a second full coat of Designa Blockseal (not thinned).
3. Apply 1 or 2 full coats of Designa Acrylic Gloss.

Fibre Cement

1. Seal with Designa Acrylic Gloss thinned 20% with water.
2. Apply 2 coats of Designa Acrylic Gloss.

Galvanised Surfaces

1. Apply one coat of Galvoprime.
2. Apply 2 coats of Designa Acrylic Gloss.

Refer to technical data sheets of the Primers.

PERFORMANCE & LIMITATIONS

Performance

- Excellent durability and gloss retention
- Exceptional intercoat adhesion
- Excellent flexibility
- Resists dirt pick up
- Suitable for potable water (with suitable primer)

Limitations

- Not to be used on doors or windows where surfaces are subject to pressure
- Should not be applied if temperatures are below 10°C
- Dry time may be impeded if the relative humidity is high

HEALTH & SAFETY

Waterborne

Designa Acrylic Gloss is a water reducible non toxic coating. It is non flammable and requires no special handling. We recommend the use of a barrier cream for hands when applying.

Transport

UN No.	:	N/A
Class	:	N/A
Hazchem	:	N/A

Storage

Avoid freezing or temperatures in excess of 50°C.