

PRODUCT LINE	Designa Ceiling Ultra Flat	
DESCRIPTION	<p>Designa Ceiling Ultra Flat is a premium quality acrylic flat for all interior ceilings. Designa Ceiling Ultra Flat incorporates the most modern additives to impart excellent opacity with a dead flat finish and low roller splatter.</p> <p>Designa Ceiling Ultra Flat comes with a 10 year guarantee.</p>	
TYPICAL USES	<p>May be used over most prepared surfaces, including:</p> <ul style="list-style-type: none"> • Gib board • Wallboard • Timber • Pinex • Fibrolite • Hardiflex • Customwood 	
PHYSICAL PROPERTIES	<p>Binder Type Solvent Colour Finish Dry Time Recoat time Number of Coats Theoretical Coverage Recommended Film Thickness Thinning & Clean Up</p>	<p>Acrylic Copolymer Water White and pastel colours Dead flat < 1% gloss at 60° 30 minutes at 20°C 2 hours at 20°C 2 10-12m² per litre 100 microns W.F.T Water</p>
SURFACE PREP	<p>Ensure surfaces are free from loose or flaky paint. Wash surfaces with Colourplus Sugar Soap prior to painting to remove oil, grease, dirt, and other contaminants. Where there are areas of mould, treat with Colourplus Green Clean.</p> <p>All new surfaces must have appropriate sealer applied before applying Designa Ceiling Ultra Flat.</p>	
APPLICATION	<p>Designa Ceiling Ultra Flat may be applied by synthetic brush or roller. Roller sleeve - a synthetic 8mm nap is recommended.</p> <p>Gib board, Wallboard & Pinex</p> <ol style="list-style-type: none"> 1. Apply 1 solid coat of Designa Interior Acrylic Sealer Undercoat, allowing 2 hours to dry. 2. Apply 1 or 2 coats Designa Ceiling Ultra Flat. Allow 2 hours between coats. <p>Timber, Fibrolite, Hardiflex & Customwood</p> <ol style="list-style-type: none"> 1. Apply 1 coat of Designa Acrylic Primer Undercoat, allowing 2 hours drying. 2. Apply 2 coats Designa Ceiling Ultra Flat. Allow 2 hours between coats. 	

**PERFORMANCE
& LIMITATIONS**

Performance

- Excellent coverage and opacity
- Easy to apply
- Dries to an even dead flat finish

Limitations

- No designed for exterior use
- Should not be applied if temperatures are below 10°C
- Dry time may be impeded if humidity is high

HEALTH & SAFETY

Water based material

Designa Ceiling Ultra Flat is a water reducible non toxic coating. It is non flammable and requires no special handling. We recommend the use of a barrier cream for hands when applying.

Transport

UN No.	:	1263
Class	:	N/A
Hazchem	:	N/A

Storage

Avoid freezing or temperatures in excess of 50°C.