



DESIGNA

Acrylic Sealer Undercoat

Interior Sealer for Walls and Ceilings
Technical Data Sheet DS366

PRODUCT LINE	Designa Interior Acrylic Sealer Undercoat	
DESCRIPTION	<p>Designa Interior Acrylic Sealer Undercoat is a fast drying high build sealer and undercoat for interior applications. Acrylic Sealer Undercoat dries to a free sanding film with good hold-out and opacity.</p> <p>Designa Acrylic Sealer Undercoat comes with a 10 year guarantee.</p>	
TYPICAL USES	<p>May be used over most prepared surfaces, including:</p> <ul style="list-style-type: none">• Timber• Previously painted surfaces• Composite boards• Plaster• Fibre Cement• Gib board• Wallpaper	
PHYSICAL PROPERTIES	Binder Type	Copolymer acrylic
	Solvent	Water
	Colour	White
	Finish	Matt
	Dry Time	30 minutes at 20°C
	Recoat time	2 hours at 20°C
	Number of Coats	1
	Theoretical Coverage	8-10m ² /litre
	Recommended Film Thickness	100 microns per coat W.F.T
	Thinning & Clean Up	Water
SURFACE PREP	<p>Ensure surfaces are free from loose or flaky paint. Wash surfaces with Colourplus Sugar Soap prior to painting to remove oil, grease, dirt, and other contaminants. Where there are areas of mould, treat with Colourplus Green Clean.</p>	
APPLICATION	<p>Designa Acrylic Sealer Undercoat may be applied by synthetic brush, roller or spray. Airless Spray - a 417 or 517 tip is recommended.</p> <p>All substrates</p> <ol style="list-style-type: none">1. Apply 1 coat of Designa Interior Acrylic Sealer Undercoat, allowing 2 hours drying. After sanding remove dust.2. Apply 2 coats of selected top coat. <p><i>Note: When applying over a substrate that has distinctly contrasting colours, tint Designa Sealer Undercoat to a light grey. This will ensure good hiding power for the top coats.</i></p>	

**PERFORMANCE
& LIMITATIONS**

Performance

- Excellent spray application
- Free sanding to a smooth surface
- Excellent hold out for top coats

Limitations

- Do not apply if temperatures are below 10°C
- Dry time may be impeded if the relative humidity is high

HEALTH & SAFETY

Water based material

Designa Interior Sealer Undercoat is a water reducible non toxic coating. It is non flammable and requires no special handling. We recommend the use of a barrier cream for hands when applying.

Transport

UN No.	:	1263
Class	:	N/A
Hazchem	:	N/A

Storage

Avoid freezing or temperatures in excess of 50°C.