

PRODUCT LINE	Designa Pigmented Sealer	
DESCRIPTION	Designa Pigmented Sealer is a modified alkyd based sealer designed for application to all porous and loosely bound surfaces. Also used to seal nicotine or water stained walls and ceilings before painting.	
TYPICAL USES	May be used on suitably prepared: <ul style="list-style-type: none">• Gib board• Pinex• Fibrous plaster• As a wall board sealer before wallpapering• Brick and cementitious products• Timber	
PHYSICAL PROPERTIES	Binder Type	Urethane modified alkyd resin
	Solvent	Mineral turpentine
	Colour	White
	Finish	Satin
	Dry Time	4 hours at 20°C
	Recoat time	16 hours at 20°C
	Number of Coats	1
	Theoretical Coverage	8-10m ² per litre
	Thinning & Clean Up	Mineral Turpentine
SURFACE PREP	Ensure surfaces are free from loose or flaky paint. Wash surfaces with Colourplus Blue Wash for exterior surfaces or Colourplus Sugar Soap for interior surfaces prior to painting to remove oil, grease, dirt, and other contaminants. Where there are areas of mould, treat with Colourplus Green Clean.	
APPLICATION	Designa Pigmented Sealer may be applied by brush, roller or spray. Airless Spray - a 415 or 515 tip is recommended	
	All substrates	
	1. Carefully sand to a smooth, even surface. Remove dust and apply 1 coat of Designa Pigmented Sealer, allow overnight to dry before over coating.	
PERFORMANCE & LIMITATIONS	Performance <ul style="list-style-type: none">• Excellent adhesion to alkyd and acrylic top coats• Easy to apply Limitations <ul style="list-style-type: none">• As a sealer, Designa Pigmented Sealer is not designed to impart opacity• Contains solvent.	

HEALTH & SAFETY

Alkyd sealer

Designa Pigmented Sealer is lead free but contains solvents. Do not expose containers to naked flame or high temperature heating equipment. We recommend the use of a barrier cream for hands when applying and that when spraying safety glasses or a face mask be worn.

Transport

UN No.	:	1263
Class	:	3
Hazchem	:	3(Y)

Storage

Avoid freezing or temperatures in excess of 50°C.