

PRODUCT LINE	Timbercare Timber Finish	
DESCRIPTION	Colourplus Timber Finish is a 100% acrylic self priming paint utilising special modifiers for maximum exterior performance. This product provides a low sheen finish and is designed as a two coat system for timber products including decks, but may be used on most building substrates, including concrete, plaster, fibre cement boards etc.	
TYPICAL USES	May be used on suitably prepared: <ul style="list-style-type: none">• Weatherboards• Timber including decks• Plywood• Galvanized iron• Concrete, concrete blocks• Textured surfaces• Fibre cement	
PHYSICAL PROPERTIES	Binder Type	100% acrylic
	Solvent	Water
	Colour	White and selected colours
	Finish	Low sheen – 10% gloss
	Dry Time	30 minutes at 20°C
	Recoat time	2 hours at 20°C
	Number of Coats	2
	Theoretical Coverage	10-12m ² per litre
	Recommended Film Thickness	100 microns per coat W.F.T
	Thinning & Clean Up	Water
SURFACE PREP	Ensure surfaces are free from loose or flaky paint. Wash surfaces with Colourplus Blue Wash prior to painting to remove oil, grease, dirt, and other contaminants. Where there are areas of mould, treat with Colourplus Green Clean.	
APPLICATION	Colourplus Timber Finish may be applied by brush, roller or spray. Airless Spray - a 415 or 417 tip is recommended for weatherboards, and a 517 tip is recommended for textured surfaces before being back rolled. Weatherboards – pre primed <ol style="list-style-type: none">1. Apply 2 coats of Colourplus Timber Finish, allow 2 hours between coats. New Timber <ol style="list-style-type: none">1. Apply 1 coat of Colourplus Timber Finish as a primer and allow 2 hours before recoating.2. Apply 2 coats of Colourplus Timber Finish and allow 2 hours between coats. Repaints <ol style="list-style-type: none">1. Sand existing paint work and spot prime bare wood with Colourplus Timber Finish.2. Apply 2 coats of Colourplus Timber Finish as above.	

Cementitious Substrates – Stucco, Fibre Cement, Concrete etc.

1. Apply 2 coats of Colourplus Timber Finish, allow 2 hours between coats.

Galvanised Surfaces (not roofs)

1. Apply one coat of Designa Galvanised Iron Primer, allow 2 hours drying.
2. Apply 2 coats of Colourplus Timber Finish.

**PERFORMANCE
& LIMITATIONS**

Performance

- Excellent durability
- Exceptional intercoat adhesion
- Excellent flexibility
- Resists dirt pick up
- Suitable for potable water

Limitations

- Not to be used on doors or windows where surfaces are subject to pressure
- Should not be applied if temperatures are below 10°C
- Dry time may be impeded if the relative humidity is high
- When applying over Cedar or highly treated timber where stain bleeding may occur seal with Permaseal first

HEALTH & SAFETY

Waterborne

Timbercare Timber Finish is a water reducible non toxic coating. It is non flammable and requires no special handling. We recommend the use of a barrier cream for hands when applying.

Transport

UN No.	:	N/A
Class	:	N/A
Hazchem	:	N/A

Storage

Avoid freezing or temperatures in excess of 50°C.