



ULTRA PREMIUM

Ultracare Satin Kitchen & Bathroom Water Based Enamel Technical Data Sheet UP337

PRODUCT LINE	Ultra Premium Ultracare Satin Kitchen and Bathroom																					
DESCRIPTION	<p>Ultra Premium Ultracare Satin Kitchen and Bathroom is a hard wearing water based enamel in a satin finish designed for use especially on wet areas such as kitchens, bathrooms and laundries. May also be used on trim where a satin finish is required.</p> <p>Ultracare Satin Kitchen and Bathroom is highly durable and specially formulated to provide protection against mould and bacteria. Ultracare Satin Kitchen and Bathroom is fast drying, non yellowing, has a very low odor and cleans up in water.</p> <p>Ultracare Kitchen and Bathroom comes with a 15 year guarantee and a 5 year guarantee against mould.</p> <p>Interior and Exterior Use</p>																					
TYPICAL USES	For wet areas such as bathrooms where a hard wearing finish and resistance to moisture is required. Also excellent for timber doors, architraves, skirting's, window frames and exterior trim.																					
PHYSICAL PROPERTIES	<table><tr><td>Binder type</td><td>Unique cross linking acrylic</td></tr><tr><td>Solvent</td><td>Water</td></tr><tr><td>Colour</td><td>White and tinted colours</td></tr><tr><td>Finish</td><td>Satin – 20% Gloss</td></tr><tr><td>Dry Time</td><td>1 hour at 20°C</td></tr><tr><td>Recoat Time</td><td>2 – 4 hours at 20°C</td></tr><tr><td>Number of Coats</td><td>2</td></tr><tr><td>Theoretical Coverage</td><td>12m² per litre</td></tr><tr><td>Recommended Film Thickness</td><td>100 microns per coat W.F.T</td></tr><tr><td>Thinning and Clean Up</td><td>Water. (In hot conditions can be thinned up to 5% with Protec Hot Weather Thinners)</td></tr></table>	Binder type	Unique cross linking acrylic	Solvent	Water	Colour	White and tinted colours	Finish	Satin – 20% Gloss	Dry Time	1 hour at 20°C	Recoat Time	2 – 4 hours at 20°C	Number of Coats	2	Theoretical Coverage	12m ² per litre	Recommended Film Thickness	100 microns per coat W.F.T	Thinning and Clean Up	Water. (In hot conditions can be thinned up to 5% with Protec Hot Weather Thinners)	
Binder type	Unique cross linking acrylic																					
Solvent	Water																					
Colour	White and tinted colours																					
Finish	Satin – 20% Gloss																					
Dry Time	1 hour at 20°C																					
Recoat Time	2 – 4 hours at 20°C																					
Number of Coats	2																					
Theoretical Coverage	12m ² per litre																					
Recommended Film Thickness	100 microns per coat W.F.T																					
Thinning and Clean Up	Water. (In hot conditions can be thinned up to 5% with Protec Hot Weather Thinners)																					
SURFACE PREP	<p>Ensure surfaces are free from loose or flaky paint. Wash surfaces with Colourplus Sugar Soap prior to painting to remove oil, grease, dirt, and other contaminants. Where there are areas of mould, treat with Colourplus Green Clean.</p> <p>Old enamels will require fine sanding to a uniform dull finish.</p>																					
APPLICATION	<p>Ultra Premium Ultracare Satin Kitchen & Bathroom may be applied by synthetic brush, roller or spray.</p> <p>Airless Spray - a 415 or 515 tip is recommended.</p> <p>Roller Sleeve - a 6mm nap micro fibre roller is recommended.</p> <p>Because of the quick drying nature of the Ultracare, in hot conditions it may be necessary to thin up to 5% with Protec Hot Weather Thinners.</p>																					

Timber, Particle Board, Customwood

1. Prime with Permaseal
2. Apply 2 coats of Ultra Premium Ultracare Satin Kitchen and Bathroom in required colour

Gib, Fibrous Plaster

1. Apply 1 coat of Designa Pigmented Sealer
2. Lightly sand and dust off
3. Apply 2 coats of Ultra Premium Ultracare Satin Kitchen and Bathroom in required colour

Previously Painted Surfaces

1. Remove any flaking paint on the surface and sand to a smooth finish
2. Prime any areas of bare wall or ceiling with Designa Pigmented Sealer
3. Old enamels require washing down with Colourplus Sugar Soap and fine sanding to a dull finish
4. Apply 2 coats of Ultra Premium Ultracare Satin Kitchen and Bathroom in required colour

PERFORMANCE & LIMITATIONS

Performance

- Ultimate hard wearing wall finish
- Can be used where traditional oil based enamels are used
- Non yellowing
- Easy application properties with excellent flow and leveling
- Excellent durability in high service areas

Limitations

- Should not be applied if temperatures are below 10°C
- Dry time may be impeded if relative humidity is high
- Ensure that the correct primer/sealer is used
- Allow putty and gap fillers to fully dry and prime putty before applying top coat
- After applying Ultra Premium Ultracare Kitchen and Bathroom water based enamel 16 hours should be allowed before the area becomes fully serviceable

HEALTH & SAFETY

Waterborne

Ultra Premium Ultracare Satin Kitchen and Bathroom is a water reducible non toxic coating. It is non flammable and requires no specific handling. We recommend the use of a barrier cream for hands when applying.

Transport

UN No.	:	N/A
Class	:	N/A
Hazchem	:	N/A

Storage

Avoid freezing or temperatures in excess of 50°C